


# TRUE WYE



Nominal Pipe Size		Outside Diameter		Thickness		Dimensions				Weight	
		D		T		A		B			
In	mm	In	mm	In	mm	In	mm	In	mm	lb	kg
3	76	3.500	89	0.120	3.0	5.50	140	3.0	76	5.20	2.40
4	102	4.500	114	0.120	3.0	6.50	165	3.0	76	7.70	3.50
5	127	5.563	141	0.134	3.4	7.50	191	3.5	89	12.30	5.60
6	152	6.625	168	0.134	3.4	8.00	203	3.5	89	15.50	7.00
8	203	8.625	219	0.148	3.8	9.00	229	4.5	114	25.70	11.70
10	254	10.750	273	0.165	4.2	11.00	279	5.0	127	43.00	19.50
12	305	12.750	324	0.180	4.6	12.00	305	5.5	140	60.80	27.60
14	356	14.000	356	0.188	4.8	14.00	356	6.0	152	80.40	36.60
16	406	16.000	406	0.188	4.8	15.00	381	6.5	165	98.90	44.90
18	457	18.000	457	0.188	4.8	16.50	419	7.0	178	122.00	55.50
20	508	20.000	508	0.218	5.5	18.00	457	8.0	203	172.90	78.60
24	610	24.000	610	0.250	6.4	22.00	559	9.0	229	286.70	130.30
30	762	30.000	762	0.312	7.9	25.00	635	10.0	254	506.30	230.20
36	914	36.000	914	0.312	7.9	28.00	711	14.0	356	710.10	322.80
42	1067	42.000	1067	0.312	7.9	31.00	787	26.0	660	1042.80	474.00
48	1219	48.000	1219	0.312	7.9	34.00	864	27.0	686	1287.80	585.30

Notes:

1. Thicknesses and Weights are for Sch 10S except 42" and 48" has 5/16" thickness.
2. Wall thickness tolerance to ASTM A-774.
3. Material : Stainless Steel 304, 304L, 316, 316L.

**FITTINGS THROUGH 100" PIPE SIZE ARE AVAILABLE**

## Sumitec Int'l, Inc

Phone (877)-837-9618 Fax (866) 311-5335 email:sumitecsales@comcast.net

**We also Supply Carbon and Stainless Steel Flanges and Pipes**