

Weld Neck Flange Bores

(Flange Size From 26" to 48")

Nominal Pipe Size	Nominal Outside Dia	Identification		Wall Thickness (In)	Inside Diameter (In)
		Std, XH & XXH	Sch		
26"	26.00		10	0.312	25.376
		Std.	40S	0.375	25.250
		XH	20/80S	0.500	25.000
28"	28.00		10	0.312	27.376
		Std.	40S	0.375	27.250
		XH	20/80S	0.500	27.000
			30	0.625	26.750
30"	30.00		10	0.312	29.376
		Std.	40S	0.375	29.250
		XH	20/80S	0.500	29.000
			30	0.625	28.750
32"	32.00		10	0.312	31.376
		Std.	40S	0.375	31.250
		XH	20/80S	0.500	31.000
			30	0.625	30.750
			40	0.688	30.624
34"	34.00		10	0.312	33.376
		Std.	40S	0.375	33.250
		XH	20/80S	0.500	33.000
			30	0.625	32.750
			40	0.688	32.624
36"	36.00		10	0.312	35.376
		Std.	40S	0.375	35.250
		XH	20/80S	0.500	35.000
			30	0.625	34.750
38"	38.00		40	0.750	34.500
		Std.	40S	0.375	37.250
		XH	80S	0.500	37.000
40"	40.00	Std.	40S	0.375	39.250
		XH	80S	0.500	39.000
42"	42.00	Std.	40S	0.375	41.250
		XH	80S	0.500	41.000
44"	44.00	Std.	40S	0.375	43.250
		XH	80S	0.500	43.000
46"	46.00	Std.	40S	0.375	45.250
		XH	80S	0.500	45.000
48"	48.00	Std.	40S	0.375	47.250
		XH	80S	0.500	47.000

Sumitec Int'l, Inc

Phone (877)-837-9618 Fax (866) 311-5335 email:sumitecsales@comcast.net

We also Supply Carbon and Stainless Steel Buttweld Fittings and Pipes